



PARAFFIN WAX CO.
MEMBER OF RAHA GROUP

DATA SHEET OF SLACK WAX LIGHT GRADE 12% OIL CONTENT

General description of slack wax **light grade 12% oil content**

Heavy slack wax has higher melting and congealing point, this grade has about 15% oil content. It is a product of petroleum refining, in last years it considered as waste of the refineries and they paid to get rid of this product but now it is so useful that most of the refineries slack wax is booked and purchased some month before producing.

Packing is the drum in the summer time and can be polyamide bags during cold seasons to prevent any deformation and leakage during delivery.

RAHA company guaranty the quality of **slack wax heavy grade 12% oil content** with the arrangement of the international inspector to check quality and quantity of the slack wax heavy grade 12% oil content during the loading to the vessel and controlling the production by QC by batch test report before shipping. RAHA Company guarantees the quality to meet with ASTM.

Application of slack wax **light grade 12% oil content**

Slack wax heavy grade 12% oil content is used in producing wax emulsion, polishing boards. Cable filling, paraffin wax and PVC industries.

Packing of slack wax **light grade 12% oil content**

Packing of heavy *slack wax heavy grade 12% oil content* is drum in summer time and can be polyamide bags during cold seasons to prevent any deformation and leakage during delivery.



Gold Supplier



Add: Second Floor, Navab Complex, Navab safavi St, Esfahan – Iran

www.paraffinwaxco.com info@paraffinwaxco.com **Tell:**+98-31-32355207 **Fax:**+98-31-32355214



PARAFFIN WAX CO.
MEMBER OF RAHA GROUP

DATA SHEET OF SLACK WAX LIGHT GRADE 12% OIL CONTENT

Specification of slack wax **light grade 12% oil content**

Characteristic	Unit	Typical	Test method
Kinematic viscosity @100 °C	Cst	7	ASTM D-445
Flash point	°C	250	ASTM D-92
Specific gravity 25 °C/25 °C	-	0.820	ASTM D-190
Oil Content	%wt	12	ASTM D-721
Congeaing Point	°C	50	ASTM D-937
Color	-	YELLOW	ASTM D-1500
Drop Melting Point	°C	50	ASTM D-127



Gold Supplier



Add: Second Floor, Navab Complex, Navab safavi St, Esfahan – Iran

www.paraffinwaxco.com info@paraffinwaxco.com **Tell:**+98-31-32355207 **Fax:**+98-31-32355214