



PARAFFIN WAX CO.
MEMBER OF RAHA GROUP

DATA SHEET OF SLACK WAX LIGHT GRADE 30% OIL CONTENT

General description of slack wax **light grade 30% oil content**

Slack wax light grade 30% oil is yellow, soft, low melting point product slack wax light grade 30% oil content is used in cold weather countries like turkey, Ukraine, Russia. Slack wax light grade is a mixture of paraffin wax and oil. since the oil content is higher the price of light slack wax is lower comparing to 10% oil content of the same grade slack wax. sometimes factories do the DE-coloring process on it and export as lower oil grade slack wax.

RAHA company guaranty the quality of *slack wax light grade 30% oil content* with the arrangement of the international inspector to check quality and quantity of the slack wax light grade 30% oil during the loading to the vessel and controlling the production by QC by batch test report before shipping. RAHA Company guarantees the quality to meet with ASTM.

Application of slack wax **light grade 30% oil content**

Slack wax light grade 30% oil is used in producing wax emulsions for particleboard and medium density fiberboard, cable filling compound, paraffin wax, matches, candles, rust protective products and moisture vapor barriers.

Packing of slack wax **light grade 30% oil content**

Because of high oil content, the only way of packing slack wax light grade 30% oil content is new or second hand 180 kg drums, iso tank or flexitanks. in each 20-foot container 110 drums of slack wax can be loaded. drums are steel one and can be new or used according to the customer's request, the difference of new and used steel drum is 25 USD/MT in the price of the slack wax.



Gold Supplier



Add: Second Floor, Navab Complex, Navab safavi St, Esfahan – Iran

www.paraffinwaxco.com info@paraffinwaxco.com **Tell:**+98-31-32355207 **Fax:**+98-31-32355214



PARAFFIN WAX CO.
MEMBER OF RAHA GROUP

DATA SHEET OF SLACK WAX LIGHT GRADE 30% OIL CONTENT

Specification of slack wax **light grade 30% oil content**

Characteristic	Unit	Typical	Test method
Kinematic viscosity @100 °C	Cst	7-8	ASTM D-445
Flash point	°C	230	ASTM D-92
Specific gravity 25 °C/25 °C	-	0.78	ASTM D-190
Oil Content	% wt	30-35	ASTM D-721
Congeaing Point	°C	50	ASTM D-937
Color	-	4	ASTM D-1500
Drop Melting Point	°C	52	ASTM D-127



Gold Supplier



Add: Second Floor, Navab Complex, Navab safavi St, Esfahan – Iran

www.paraffinwaxco.com info@paraffinwaxco.com **Tell:**+98-31-32355207 **Fax:**+98-31-32355214